



Visit product page



DM8

L005638

Digital mixing console , 8 channel - 6 mic inputs, 1 stereo inputs, 2 XLR outputs, 2 bus, 4 Effects Modules ,2 reverb ,2 Delay, WIFI connecting to USB wireless module,1 LAN interface

TECHNICAL DETAILS

Technical Specifications

Microphone input: 6 channels, 2 Combo XLR.

Channel input: 1 pair of stereo, 2 jacks.

Main output: 2 XLR.

AUX output: 2 jack outputs.

Footswitch: 2 jacks.

Monitor: 1 jack.

Mic input impedance: 3K.

Line input impedance: 20K.

Output impedance: 75Ω.

Headphone output impedance: 100Ω.

BUS remaining output noise: -90 dBu.

Maximum voltage gain: 80dB input to output.

Dynamic Range: 106dBu (20Hz - 20 kHz).

AD/DA: Maximum 24bit / 48 kHz supported.

Signal processing: 40bit floating point processor.

Signal latency: <1.8 msec input to output.

Phantom power supply: 48V, each channel can be switched individually.

Crosstalk @1kHz: -85dB.

USB interface: 2 USB 2.0 interface, maximum 32G supported, can be used for USB disk playback and recording, supports WAV & MP3 formats

Network: WiFi connecting to USB wireless module, 1 LAN interface.

Effects: 4x effect modules, 2 reverb, 2 delay.
Power supply: DC adapter (AC 100/240 Volt AC, 50/60 Hz).

PHOTOS



PRODUCT VIDEO



ACCESSORIES



DM8 Rack

19-inch rack brackets for
DM8 mixing console.

